

In the claims:

For the Examiner's convenience, all pending claims are presented below with changes shown.

- 1 1. (Original) A method comprising:

2 receiving a first identification (ID) at a computer system from a server via a
3 transmission medium;
4 comparing the first ID with a second ID stored at a first analog front end coupled
5 to the computer system; and
6 certifying a first software-defined radio for operation if the first ID matches the
7 second ID.
- 1 2. (Original) The method of claim 1 further comprising disabling the first
2 software-defined radio if the first ID does not match the second ID.
- 1 3. (Original) The method of claim 1 further comprising storing the first ID in a
2 memory device within a baseband unit at the computer system prior to comparing the
3 first ID with the second ID.
- 1 4. (Original) The method of claim 1 further comprising downloading a protocol
2 corresponding with the first software-defined radio.
- 1 5. (Original) The method of claim 4 wherein the first ID and the wireless
2 protocol are received as a component of a signed manifest.
- 1 6. (Original) The method of claim 5 further comprising:
2 validating the signed manifest; and
3 executing the protocol at a baseband unit if the manifest is validated.

1 7. (Original) The method of claim 1 further comprising:
2 receiving a third identification (ID) at the computer system from the server via the
3 transmission medium;
4 comparing the third ID with a fourth ID stored at a second analog front end
5 coupled to the computer system; and
6 certifying a second software-defined radio for operation if the third ID matches
7 the fourth ID.

1 8. (Original) A computer system comprising a first software-defined radio
2 including:
3 a baseband unit; and
4 a first analog front-end coupled to the baseband unit;
5 the first software-defined radio being certified for operation by authenticating a
6 first identification (ID) received at the baseband unit with a second ID stored at the first
7 analog front end.

1 9. (Original) The computer system of claim 8 further comprising:
2 an input/output (I/O) bus coupled to the baseband unit; and
3 a network controller coupled to the I/O bus.

1 10. (Original) The computer system of claim 9 wherein the first ID is received
2 from a server computer via a transmission medium coupled to the network controller.

1 11. (Original) The computer system of claim 10 wherein a protocol
2 corresponding to the first software-defined radio is also received from the server
3 computer.

1 12. (Original) The computer system of claim 9 wherein the baseband unit
2 comprises:

an I/O interface coupled to the I/O bus;
a digital signal processor (DSP) coupled to the I/O interface; and
a second bus coupled to the DSP.

13. (Original) The computer system of claim 12 wherein the baseband unit further comprises:

a volatile memory coupled to the DSP; and
a non-volatile memory coupled to the DSP.

14. (Original) The computer system of claim 12 wherein the analog front end comprises:

analog-digital/digital-analog (AD/DA) conversion logic coupled to the second bus;
modulation logic coupled to the AD/DA conversion logic;
a transceiver coupled to the modulation logic; and
an antenna coupled to the transceiver.

15. (Original) The computer system of claim 14 wherein the analog front end comprises a non-volatile memory that stores the second ID.

16. (Original) The computer system of claim 12 further comprising a second software-defined radio including:
the baseband unit; and
a second analog front-end coupled to the baseband unit;
the second software-defined radio being certified for operation by authenticating a third ID received at the baseband unit with a fourth ID stored at the second analog front end.

17. (Original) A network comprising:

2 a first client computer;
3 a transmission medium coupled to the first client computer; and
4 a server computer, coupled to the transmission medium, that transmits first
5 identification (ID) data to the first client computer upon receiving a request from the
6 client computer to certify a first software-defined radio implemented at the first client
7 computer.

1 18. (Original) The network of claim 17 further comprising a second client
2 computer coupled to the transmission medium, the server computer transmits the first ID
3 data to the second client computer upon receiving a request from the second client
4 computer to certify the first software-defined radio implemented at the second client
5 computer.

1 19. (Original) The network of claim 17 wherein the server computer transmits
2 second ID data to the first client computer upon receiving a request from the first client
3 computer to certify a second software-defined radio implemented at the first client
4 computer.

1 20. (Original) A method comprising:
2 receiving a request at a server computer to certify a first software-defined radio
3 implemented at a first client computer; and
4 transmitting first identification (ID) data corresponding to the first software-
5 defined radio to the first client computer.

1 21. (Previously Presented) The method of claim 21 further comprising
2 transmitting a radio protocol corresponding to first software-defined radio to the first
3 client.

1 22. (Original) The method of claim 20 further comprising:

2 receiving a request at the server computer to certify the first software-defined
3 radio implemented at a second client computer; and
4 transmitting the first ID data to the second client computer.

1 23. (Original) The method of claim 20 further comprising:
2 receiving a request at the server computer to certify a second software-defined
3 radio implemented at the first client computer; and
4 transmitting second ID data corresponding to the second software-defined radio to
5 the second client computer.